

Assessment of ground water quality in Bachigudam village near Patencheru in Medak district in month of September

Baby Abrarunnisa Begum^{*}, N. Devanna^{**}, Md. Sibgatullah^{***}, Asma^{***}

^{*}NCET, JNTU; ^{**}Director, JNTU-A; ^{***}Post-MBBS research scholars, Andhra Pradesh, INDIA.

Email: sibgatullah2@yahoo.com

Abstract

Rapid industrialization has resulted in pollution of ground water resources. Patencheru in medak district is one such industrial hub near Hyderabad. The treated industrial waste in released into stream nakkavagu which joins river manjeera a tributary of river Godavari. Bachigudem village was selected for ground water assessment as it lies in the nakkavagu catchment area. Parameters from eight sources were analysed for parameters such as color, turbidity, pH, total alkalinity, total dissolved solids, total hardness, chlorides, sulphates, nitrates, fluorides and electrical conductivity. The sampling was done in month of september which is almost end of rainy season. The results showed gross contamination of the ground water in bachigudem village.

Key Word: Ground water quality, pH, alkalinity.

*Address for Correspondence

Md. Sibgatullah, Post-MBBS research scholars, Andhra Pradesh, INDIA.

Email: sibgatullah2@yahoo.com

Received Date: 19/05/2014 Accepted Date: 23/05/2014

Access this article online	
Quick Response Code:	Website: www.statperson.com
	DOI: 01 June 2014

INTRODUCTION

As the distribution of surface sources of water is so uneven as to be inadequate, in many parts of the country the dependence on groundwater is almost total. This is especially true in regions of arid to semi-arid type of climate where average annual rainfall is less than 100 cm and the scope of aquifer recharge is limited. Thus, groundwater continues to be exploited at ever increasing rates, especially in the rapidly expanding urban areas of the country. But rapid urban sprawl and industrialization have the unfortunate fallout of environmental pollution. In the absence of appropriate waste management

strategies, many human activities and their by-products have the potential to pollute surface and subsurface water. Industrial effluents, and wastes from urban infrastructure, agriculture, horticulture, transport and discharges from abandoned mines and deliberate or accidental pollution, all eventually affect the water quality. The pollutants from the stream may move slowly in to the ground, thus affecting the quality of groundwater. Depending on various natural and cultural factors, the quality of groundwater in terms of its physical, chemical and organic characteristics is variable, determining its suitability for different purposes— domestic, agricultural or industrial.¹ Ground water is one of the essential components for the sustenance of life on earth. Among the various sources of water, ground water is said to be the safest water for drinking and domestic purposes. The quality of ground water is influenced by the nature of the sub surfaces as well as the environment where recharge takes place. Water used for industries, agricultural and human needs adds continuously contaminants to the ground water. It is reported that two third of all illness in India are related to water borne diseases.²

The major problem with the ground water is that once contaminated, it is difficult to restore its quality. Hence there is a need and concern for the protection and

management of ground water quality.³ Industrial estate at patencheru was established in the year 1975 by the Andhra Pradesh industrial infrastructure corporation ltd.,(APIIC). Patencheru is located on Mumbai-hyderabad highway around 35km from Hyderabad in medak district. Around 350 industries are located here. A common effluent treatment plant was commissioned in the year 1990, to treat industrial waste water. There are two natural water courses in the area namely nakkavagu and isukavagu and normally for most part of the year they are dry with no fresh water flowing into them. After treating the the industrial effluents the water is discharged into nakkavagu stream. The entire patencheru industrial area provided with all the necessary infrastructural facilities except the much needed sewer system. The study has been done in bachigudem village in the nakkavagu catchment area in the month of july which is a peak rainy season.

MATERIALS AND METHODS

A systematic survey of bachigudem village was conducted in month of September 2012. Eight locations having borewells were identified and assigned identity numbers. Water samples were collected from the borewells on a single day.

S-1: Hanuman temple bore well

S-2: S.C colony bore well

S-3: Chinta pentayya house bore well

S-4: kotta basti bore well

S-5: Vittal reddy house borewell

S-6: Narasimha reddy house near school bore well

S-7: Karunakar Reddy home bore well

S-8: narasimha reddy home near mosque bore well

Parameters Analysed

Parameters analyzed are color, turbidity, total hardness, pH, electrical conductivity, total alkalinity, total dissolved solids, chlorides, fluorides and sulphates. All the samples were analyzed as per Standard Method *APHA 1998*. (4) The results thus obtained have been compared with WHO guidelines for drinking water as in the absence of supplied water borewell water is being used for drinking and other house hold purposes.

RESULTS AND DISCUSSION

The analytical results thus obtained are averaged for rainy season:

pH In all the samples pH is in the desirable limit. This is due to dilution because of rain.

Color It is well within the standards (desirable limit 5 Hazen Units).

Turbidity It is well within the standards in all the samples (desirable limit 5 NTU).

Total Hardness Total hardness, an important property indicating the quality of groundwater is mainly caused by calcium and magnesium cat ions and is defined as the sum of their concentrations expressed in mg/l. Basically, it is the soap consuming property of water(5).In all the bore well samples total hardness has exceeded the standard value in the rainy season (desirable limit 300 mg/l)

Total Alkalinity In all the samples total alkalinity in all the samples is well within the standard limit, (desirable limit 200 mg/l).

Total Dissolved Solids all the bore well samples have shown the trend of exceeding the standard limit (desirable limit 500mg/l)

Chlorides The WHO limit for chloride in groundwater is < 250mg/l. In the entire bore well water sample it is above the standards (desirable limit 250mg/l)

Fluorides all the samples are well within the standards (desirable limit 1.0 mg/l) According to UNESCO specifications water containing more than 1.5 mg/l of fluoride can cause mottled tooth enamel in children. Excess fluoride may also lead to flourosis that can result in skeletal damage.

Sulphates In S4.S5 samples are within the standards and remaining samples (S1, S2, S3, S6 and S7) are above the standards. (250mg/l). Concentrationsexceeding 500 – 600 mg/limpart a bitter taste and maycause laxative effects in someindividuals (6).

Nitrate Nitrate in natural water is due to organic sources or from industrial and agricultural chemicals (7).All the bore well water sample are well within the standards (desirable limit 45 mg/l)

Electrical Conductivity (EC) depends upon temperature, ionic concentration and types of ions present in the water (8). Thus the EC gives a qualitative picture of the quality of groundwater. The electrical conductivity exceeded the upper limit in all the samples.

From the Tables 1 t is observed that other than color, turbidity, alkalinity and fluorides which are within the drinking water standards, all other parameters are exceeding the drinking water standards desirable limit. It is necessary to intervene and see that the ground water does not get polluted further more

CONCLUSION

The ground water obtained from the above sources in the month of september appears grossly contaminated. The effluents should be treated properly before releasing them into streams. Quality checks should be performed in the existing effluent treatment plants. People should be advised not to use the ground water for drinking purposes. Regular checks should be done to assess the water quality in the susceptible areas.

REFERENCES

1. G. Udayalaxmi, D. Himabindu and G. Ramadass; Geochemical evaluation of groundwater quality in selected areas of Hyderabad, A.P., India”, Indian Journal of Science and Technology, Vol. 3 No. 5 (May 2010), 546-553.
2. MFR Sowers; MK Clark; Am J Epidemiol, 1991; 133: 649–60.
3. K. Jothivenkatachalam, A. Nithya and S. Chandra Mohan, “Correlation analysis of drinking water quality in and around Perur block of Coimbatore District, Tamil Nadu, India,” Rasayan Journal Chemistry, vol. 3(4), pp. 649-654, 2010.
4. APHA (1998) Standard methods for the examination of water and wastewater. Amer. Pub. Health Assoc.
5. Fletcher GD (1986) Groundwater and wells, 2nd ed., Johnson Division Publ., Sr. Paul, Minnesala. pp:1089.
6. Raghunath HM (1987) Groundwater. Wiley-Eastern Ltd., New Delhi.
7. Feth JH, Nitrogen compounds in natural water –a review. 1966. Water Res. 2(1), 41-48.
8. Hem JD, Study and interpretation of the chemical characteristics of natural water. 1991. Scientific Publ., Jodhpur.

Source of Support: None Declared
Conflict of Interest: None Declared